

CODE	WonderPaint Names	Actual VOC	VOC Limits*	EPA Type
W15789	ASA 606; ASA606+	25	250 gm/L	Roof coatings
W15868	T'Rubber	0	200 gm/L	Primers and undercoaters
W15787	LikeNu(Standard - REPELLENT)	50	250 gm/L	Waterproofing sealer
W15788	LikeNu (NON-REPELLENT)	0	50 gm/L	Waterproofing sealer
W15859	ASA 603 CEP	0	200 gm/L	Primers and undercoaters
W15790	NuKlear (Standard - Matte)	140	250 gm/L	Waterproofing sealer
W15791	NuKlear (Gloss)	160	250 gm/L	Waterproofing sealer
W15852	NuKlear Saturating Prime	60	250 gm/L	Stains, Waterproofing sealer
W15850	Wonder25 DEEP BASE	40	250 gm/L	Mastic Texture Coating
W15845	Wonder25 PASTEL BASE	155	250 gm/L	Mastic Texture Coating
U15856	Pebble Beach ALIPHATIC URETHANE	20	250 gm/L	Floor Coating
W15857	AUS (Acrylic - Urethane)	60	250 gm/L	Floor Coating
W15858	FLEXCLEAR URETHANE SATIN	250	250 gm/L	Floor Coating
V15861	Aziridine Cross Linker	0	NA	NA
W15846	FIBER FLEX PRIMER 505A	0	200 gm/L	Primers and undercoater
W15847	FIBER FLEX 505B	135	150 gm/L	exterior nonflat coating

Limits are expressed in grams of VOC per liter¹ of coating thinned to the manufacturer's maximum recommendation, excluding the volume of any water, exempt compounds, or colorant added to tint bases.

* These limits are based on California requirements effective Jan. 1, 2003. Similar rules are currently effective in NY, NJ, PA, VA, DE and DC. They're under consideration in several other states to be effective in 2006.

WonderPaint Inc
249 Old Zion Church Road
Woodburn, KY 42170
ph/fax 270 529-3816
www.wonderpaint.com