



PRODUCT PROFILE

GENERIC DESCRIPTION Cement modifier to create a cementitious paint.

COMMON USAGE Floor surfacing, thin floor topping, anti-corrosive overlays, concrete recoloring and decorative effects.

PERFORMANCE Seals concrete surfaces; increases surface strength, flexibility and vibration resistance; chemical resistance

APPLICATION

CLEANING Wire brush all loose scale, degrease, wash and dry. Surface should be firm, clean, dry and abraded. Repair spalled or damaged concrete with ASA603 Polymer concrete before application.

PRIMING Apply ASA 603 CEP cut 50% with water to prime surface.

MIXING Mix 3.5 lb. #1 Portland Cement with 1/2 gallon water. Allow this to sit for 20 minutes.

Blend with 1 gallon LikeNu.

APPLICATION Can be applied with roller or spray application. Minimum of 2 coats. 100-150 sq. ft coverage per gallon of LikeNu.

POT LIFE Up to 6 hours. If it thickens thin with water.

FINISH Sealing with an acrylic or urethane top coat recommended.

TECHNICAL DATA

Typical LikeNu Properties

Tensile Strength	4,500 to 5,000 psi
Modulus of Elasticity	GPa 275,000 to 450,000 psi
Compressive Strength	7,500 to 12,000 psi
Elongation	2.5% to 5%
Water absorption	Minimal
Freeze-thaw Resistance	Very good
Acid Resistance	Good
Oil Resistance	Resists gasoline, oil and brake fluid

WEIGHT - PERCENT SOLIDS 50.1%

VOC's 50gm/L [EPA category: Waterproofing sealers. VOC limit 250 gm/L]

PACKAGING 5 gallon (18.9L) pails and 1 gallon (3.79L) cans.

NET WEIGHT PER GALLON* 10.61 lb

SHELF LIFE 24 months at recommended storage temperature. 40-90 F°

FLASH POINT - SETA N/A

OPTIONS Color and anti-graffiti packages are available and added upon request.

COLORS: LikeNu is similar to a white base. You control tone by using either white or gray Portland cement. LikeNu can be colored with standard concrete or latex paint colorants. Brighter white and colors can be achieved by replacing 1/2 lb. of the cement with NuCrete III. We can precolor it for you. Call for color matching.

HEALTH & SAFETY Paint products contain chemical ingredients which are considered hazardous. Read container label warning and Material Safety Data Sheet for important health and safety information prior to the use of this product. Keep out of the reach of children.

Published technical data and instructions are subject to change without notice. The online catalog at <http://www.wonderpaint.com> should be referenced for the most current technical data and instructions or you may contact your WonderPaint representative.

WonderPaint Inc
249 Old Zion Church Road
Woodburn, KY 42170
ph/fax 270 529-3816
www.wonderpaint.com