

NuKlear Data Sheet

Product Profile

Generic Description: Modified Acrylic waterproof coating.

Common Usage: Wood deck and shingle sealer. Also used on concrete and bituminous surfaces.

Colors: Clear or Stained

Performance: 5 years on vertical surfaces without primer. UV lab results available.

Coating System

TOPCOAT: Generally used as a top coat material over NuKlear Saturating Primer particularly over cellulose materials.

Surface Preparation

Wood: Clean with a sodium percarbonate cleaner. Pressure wash. Apply over NuKlear SP.

All Surfaces: Must be clean, dry and free of oil, grease and other contaminants.

Technical Data

Weight Solids: 37% ± 1

Theoretical Coverage: 300 sq.ft. per gallon @ 3 mil DFT

	Temperature	To Handle	To Recoat	To Cure
Curing Time:	75°F	45 min	immediate	7 days
Curing time varies with surface temperature, air movement, humidity and film thickness.				

Number of Components: One

Packaging: 5 gallon (18.9L) pails and 1 gallon (3.79L) cans.

Weight per gallon: 8.28 ± 0.25 lbs

Storage Temperature: Minimum 40°F Maximum 110°F

Temperature Resistance: (Dry) Continuous 200°F Intermittent 250°F

Shelf Life: 24 months at recommended storage temperature.

VOC Level: [Standard Matte] 140 gm/L

Flash Point SETA: Not Applicable

Health & Safety: Paint products contain chemical ingredients which are considered hazardous. Read Material Safety Data Sheet for important health and safety information prior to the use of this product. Keep out of the reach of children.

Published technical data and instructions are subject to change without notice. The on line catalog at www.wonderpaint.com should be referenced for the most current technical data and instructions or you may contact your WonderPaint representative.

WonderPaint Inc
249 Old Zion Church Road
Woodburn, KY 42170
ph/fax 270 529-3816
www.wonderpaint.com