

# Material Safety Data Sheet

WonderPaint, Inc.  
249 Old Zion Church Road  
Woodburn, Kentucky 42170

Date: Mar. 28, 2008 ver 1.1  
Telephone: 270 529-3816  
Night: 270 792-5451

## AUS :: Acrylic-Urethane Sealer

### SECTION 1: PRODUCT IDENTIFICATION

Trade Name:	AUS :: Acrylic-Urethane Sealer
Manufacturer:	WonderPaint, Inc.
Chemical Family:	Acrylic Polymer in Water
Dot Shipping Name:	Polymer product in water
Dot I.D. Number	Non-regulated
Appearance	Milky or Colored Fluid

### SECTION 2: HAZARDOUS INGREDIENTS:

### SECTION 3: PRECAUTIONARY INFORMATION:

Product is not considered hazardous under normal conditions. Direct contact of product with eyes can cause irritation. Prolonged or repeated contact with skin may cause irritation.

### SECTION 4: EMERGENCY AND FIRST AID PROCEDURES:

#### *First Aid:*

Eye:	Flush immediately with water for 15 minutes. Consult a physician if irritation persists.
Skin	Wash affected area with soap and water. Wash contaminated clothing before reuse.
Inhaled:	Respiratory protection is not normally required.
Fire:	Product is non-flammable in the liquid state. Use water spray, foam, dry chemical or carbon dioxide if dry.
Spill:	Collect and remove using inert absorbent. Prevent from entering sewers.

# Material Safety Data Sheet

WonderPaint, Inc.  
249 Old Zion Church Road  
Woodburn, Kentucky 42170

Date: Mar. 28, 2008 ver 1.1  
Telephone: 270 529-3816  
Night: 270 792-5451

## AUS :: Acrylic-Urethane Sealer

### SECTION 5: PERSONAL PROTECTION EQUIPMENT

Eye: Wear chemical safety goggles to reduce the potential for eye contact. Eye wash fountain ; should be available  
Skin: Use impermeable chemical gloves and wear appropriate protective clothing.  
Respiratory: Use NIOSH/MSHA approved respirator if warranted  
Ventilation: Standard industrial ventilation is recommended.

### SECTION 6: FIRE PROTECTION

Flash Point: Non-flammable  
Extinguishing Media: Non-flammable in liquid state; use water spray, foam, dry chemical. Use carbon dioxide on dried product.  
Unusual fire and explosion: Hazard Personnel exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to a rupture.

### SECTION 7: REACTIVITY INFORMATION

Stability: Stable  
Incompatibility: Not Established  
Hazardous decomposition: Thermal breakdown of this product during fire or very high heat conditions may evolve low molecular weight hydrocarbons such as carbon monoxide and carbon dioxide.

### SECTION 8: EFFECT OF OVEREXPOSURE

Eyes: Eye contact with liquid may cause irritation  
Skin: Repeated or prolonged skin contact with liquid may cause irritation or allergic sensitization.  
Inhalation: Repeated or prolonged exposures to high concentrations may cause allergic sensitization.  
Chronic: No anticipated effects.

# Material Safety Data Sheet

WonderPaint, Inc.  
249 Old Zion Church Road  
Woodburn, Kentucky 42170

Date: Mar. 28, 2008 ver 1.1  
Telephone: 270 529-3816  
Night: 270 792-5451

## AUS :: Acrylic-Urethane Sealer

### SECTION 9: PHYSICAL

Physical State: Milky liquid  
Weight/Gallon 8.61 lbs./gal.  
pH: 6.96  
Viscosity: Water  
Boiling Point: >200 F  
Solubility in water: Dilutable

### SECTION 10: SPILL AND DISPOSAL

Small Spills: Should be contained using commercially available absorbent. Shovel into recovery drum for disposal.  
Large Spills: Should be diked to prevent further movement and recovery into salvage drums.  
Disposal: This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR261. Consult your state or local authorities for proper disposal in the event more restrictive requirements apply.

### SECTION 11:

Protect from freezing - product's stability may be affected.

### SECTION 12: REGULATORY

*TOSCA* This product meets the compositional requirements of the Toxic Substances Control Act and contains only chemical ingredients that are listed on the TOSCA inventory.  
*SARA TITLE III SECTION 313:* This product does not contain toxic chemical(s) at or above the ed minimus concentrations subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372  
*California Prop. 65* "Warning": This product contains trace amounts of a chemical(s) known to California to cause cancer and/or birth defects or other reproductive harm.

WonderPaint, Inc. believes that the information provided is accurate and reliable as of the date of this material safety date sheet and is the information is given in good faith. No warranty expressed or implied is made as to the accuracy, reliability, or completeness of the information. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State and local laws and regulations. WonderPaint, Inc. urges persons receiving this information to make their own determination as to the information's suitability and applicability for an intended use.